

I – PRODUCTO

Ref. SANICEN	N/A
Producto	GUANTE DESECHABLE
Composición	LÁTEX
Color	AZUL
Unidades por envase	50 Uds.
EPI	GUANTES DE PROTECCION - CAT III (TIPO C)
Disp. Médico	N/A
Características Básicas	UN SOLO USO
	AMBIDIESTRO
	SIN ESTERILIZAR
	SIN POLVO
	A.Q.L. 1.5



Descripción del producto:

Guante de látex elástico que ofrece una alta sensibilidad al usuario y que se adapta a la mano sin oprimirla. Puño con reborde antigoteo y reforzado que evita que el guante se enrolle, a la vez que permite una colocación fácil. Presenta superficie externa e interna lisa y suave (confortabilidad).

Uso y aplicaciones según categoría:

- General:** Minimizar la exposición de las manos del usuario frente a suciedad, polvo, cuerpos extraños, humedad y agua durante la ejecución de tareas domésticas y/o industriales.
- EPI CAT III:** Proteger la mano del usuario frente a los riesgos y/o peligros detallados en el etiquetado siempre y cuando el producto se use acorde a las instrucciones de uso.

Recomendaciones de uso y almacenamiento:

- Guantes desechables (un solo uso - no reutilizar).
- Verificar la integridad del producto antes usar.
- Usar el guante con las manos secas y limpias.
- Retirar el guante doblando el manguito para dar la vuelta al producto (no tocar la parte exterior).
- Tras de su uso, lavar e hidratar las manos.
- Mantener el producto en el embalaje original, en lugares secos y no exponer a la luz directa.
- Debido a su baja capacidad de absorción, el guante debe llevarse durante un periodo limitado de tiempo, dejando descansar las manos.

Composición y alergias:

Guante de látex natural **no recomendado para personas alérgicas al látex.**

Características físicas:

Talla	Peso (g)	Longitud (mm)	Anchura (mm)	Grosor (mm)		
				Dedo	Palma	Puño
S	11,4 ±0,5	300 ±10	85 ±5	0,22 ±0,03	0,20 ±0,03	-
M	13,0 ±0,5	300 ±10	95 ±5	0,22 ±0,03	0,20 ±0,03	-
L	13,6 ±0,5	300 ±10	105 ±5	0,22 ±0,03	0,20 ±0,03	-
XL	14,6 ±0,5	300 ±10	115 ±5	0,22 ±0,03	0,20 ±0,03	-

Tallaje:

Talla comercial del guante	XS	S	M	L	XL
Talla de la mano según EN ISO 21420:2020	5 - 6	6 - 7	7 - 8	8 - 9	9 - 10

Talla de la mano según EN ISO 21420:2020	5	6	7	8	9	10
Longitud de la mano (mm)	149	160	171	182	192	204
Perímetro de la mano (mm)	127	152	178	203	229	254

Información logística y presentación:

- 50 guantes por caja dispensadora (estuche de cartón reciclable).
- Caja dispensadora con pre-troquelado en la parte superior para una fácil y cómoda extracción del guante.
- Etiquetado en varios idiomas: ES, EN, PT, IT y FR.
- Indicación clara de la talla en la caja dispensadora y la caja secundaria.
- La caja dispensadora incluye un medidor de manos para facilitar la elección de la talla.



Ref	EAN	DUN	Uds/Est	Est/caja	Caja/palet
390 (S)	8431026003904	28431026003908	50	10	35
391 (M)	8431026003911	28431026003915	50	10	35
392 (L)	8431026003928	28431026003984	50	10	35
394 (XL)	8431026003942	28431026003946	50	10	35

II – DATOS TÉCNICOS

Conformidad del producto:

Producto EPI	Descripción
Reglamento (UE) 2016/425	Relativo a los equipos de protección individual y por el que se deroga la Directiva 89/686/CEE.
EN ISO 21420:2020	Requisitos generales para los guantes de protección y métodos de ensayo.
EN ISO 374-1:2016/A1:2018	Terminología y requisitos de prestación para riesgos químicos.
EN ISO 374-2:2019	Determinación de la resistencia a la penetración.
EN 16523-1:2015+A1:2018	Resistencia a la permeabilidad de productos químicos.
EN 374-4:2013	Determinación de la resistencia a la degradación por productos químicos.
EN 374-5:2016	Terminología y requisitos de prestaciones para riesgos por microorganismos.
ISO 16604	Test de penetración viral.
Alimentos	Descripción
Reglamento (UE) 10/2011	Sobre materiales y objetos plásticos destinados a entrar en contacto con alimentos.
Reglamento (UE) 1935/2004	Sobre materiales y objetos destinados a entrar en contacto con alimentos.

En caso de necesitar profundizar en la información técnica aquí reflejada o necesita tener acceso a la declaración de conformidad correspondiente, póngase en contacto con nuestro Departamento de Calidad a través de la dirección qa@sanicen.com

Permeación y degradación del producto:

Acorde a EN ISO 374-1:2016/A1: 2018 (TIPO C)					
	QUÍMICO	COD	NIVEL (Permeación)	Degradación (%)	
	Hidróxido Sódico 40%	K	2	-34,12	
	-	-	-	-	
Nivel	1	2	3	4	5
Tiempo	>10	>30	>60	>120	>240

Contacto con alimentos: Apto para contacto con alimentos secos, acuosos, alcohólicos y productos lácteos en base al Reglamento (UE) n°10/2011 del 14 de Enero de 2011 y sus posteriores modificaciones.

Contenido del etiquetado:

Denominación del producto
Nombre y dirección del fabricante
Talla y medidor de talla
Número de lote
Número de unidades de guantes que contiene el dispensador
Fecha de fabricación y caducidad
Instrucciones de uso y condiciones de almacenaje
Código de barras (EAN 13)
Indicación A.Q.L. 1,5

Parámetros físicos adicionales:

PROPIEDAD	Antes del envejecimiento	Después del envejecimiento
Tensión de ruptura (ASTM)	18 MPa (mín.)	14 MPa (mín.)
Flexibilidad a la ruptura (ASTM)	650% (mín.)	500% (mín.)

Etiquetado:

Pictogramas* del envase:			
			
			
			
			

*Los pictogramas aquí representados tienen carácter informativo. El etiquetado del producto puede incluir información técnica específica requerida por la normalización del pictograma.

PRODUCT SPECIFICATION
PRODUCT: BLUE POWDER-FREE LATEX GLOVE

BRAND: SANYC

I – PRODUCT

Ref. SANICEN	N/A
Product	DISPOSABLE GLOVE
Composition	LATEX
Colour	BLUE
Units/inner box	50 Units.
PPE	PPE GLOVE - CAT III (TYPE C)
Medical Device	N/A
Basic Features	NON-REUSABLE
	AMBIDEXTROUS
	NON-STERILE
	POWDER-FREE
	A.Q.L. 1.5



Product description:

Elastic latex glove that provides high sensitivity to the user and conforms to the hand without causing discomfort. The cuff features an anti-drip and reinforced edge, preventing the glove from rolling up while facilitating easy placement. It has a smooth and soft external and internal surface (comfort).

Use and application by category:

- **General:** Minimize the exposure of the user's hands to dirt, dust, foreign bodies, moisture, and water during the execution of household and/or industrial tasks.
- **PPE CAT III:** Protect the user's hands against risks and/or hazards detailed in the labelling, provided that the product is used in accordance with the use instructions.

Use and storage recommendations:

- Disposable gloves (single use – do not reuse).
- Verify the integrity of the product before use.
- Use the glove with dry and clean hands.
- Remove the glove by folding the cuff to turn the product inside out (do not touch the outer part).
- After use, wash and hydrate your hands.
- Keep the product in the original packaging, in dry places and avoid exposure to direct light.
- Due to its low absorption capacity, the glove should be worn for a limited period, allowing the hands to rest.

Composition and allergies:

Natural latex glove **not recommended for people allergic to latex.**

Physical measures:

Size	Weight (g)	Length (mm)	Width (mm)	Thickness (mm)		
				Finger	Palm	Cuff
S	11,4 ±0,5	300 ±10	85 ±5	0,22 ±0,03	0,20 ±0,03	-
M	13,0 ±0,5	300 ±10	95 ±5	0,22 ±0,03	0,20 ±0,03	-
L	13,6 ±0,5	300 ±10	105 ±5	0,22 ±0,03	0,20 ±0,03	-
XL	14,6 ±0,5	300 ±10	115 ±5	0,22 ±0,03	0,20 ±0,03	-

Size:

Commercial size	XS	S	M	L	XL
Hand size according to EN ISO 21420:2020	5 - 6	6 - 7	7 - 8	8 - 9	9 - 10

Hand size according to EN ISO 21420:2020	5	6	7	8	9	10
Hand length (mm)	149	160	171	182	192	204
Hand perimeter (mm)	127	152	178	203	229	254

Logistic information:

- 50 gloves per dispenser box (recyclable cardboard case).
- Dispenser box with pre-cut on the top for an easy glove extraction.
- Labelling in multiple languages: ES, EN, PT, IT, and FR.
- Clear indication of size on the dispenser box and the secondary box.
- The dispenser box includes a hand gauge to facilitate size selection.



Ref	EAN	DUN	Gloves	Disp./Box	Box/Pallet
390 (S)	8431026003904	28431026003908	50	10	35
391 (M)	8431026003911	28431026003915	50	10	35
392 (L)	8431026003928	28431026003984	50	10	35
394 (XL)	8431026003942	28431026003946	50	10	35

PRODUCT SPECIFICATION
PRODUCT: BLUE POWDER-FREE LATEX GLOVE

BRAND: SANYC

II – TECHNICAL DATA

Legislation and standards:

PPE	Info
Reg. (UE) 2016/425	Personal protective equipment and repealing Council Directive 89/686/EEC.
EN ISO 21420:2020	Protective gloves - General requirements and test methods.
EN ISO 374-1:2016/A1:2018	Protective gloves against dangerous chemicals and micro-organisms.
EN ISO 374-2:2019	Determination of resistance to penetration.
EN 16523-1:2015+A1:2018	Determination of material resistance to permeation by chemicals.
EN 374-4:2013	Determination of resistance to degradation by chemicals.
EN 374-5:2016	Terminology and performance requirements for micro-organisms risks.
ISO 16604	Determination of resistance of protective clothing materials to penetration by blood-borne pathogens.
Food Contact	Info
Reg. (UE) 10/2011	Plastic materials and articles intended to come into contact with food.
Reg. (UE) 1935/2004	Materials and articles intended to come into contact with food.

If you need to delve deeper into the technical information provided here or require access to the corresponding declaration of conformity, please contact our Quality Department at qa@sanicen.com

Permeations and degradation:

According to EN ISO 374-1:2016/A1: 2018 (TYPE C)						
	PRODUCT		COD	LEVEL (Permeation)	Degradation (%)	
	Sodium hydroxide 40%		K	2	-34,12	
	-		-	-	-	
	-		-	-	-	
Level	1	2	3	4	5	6
Time	>10	>30	>60	>120	>240	>480

Food contact: Suitable for contact with dry food, aqueous, alcoholic and milk products based on Regulation (EU) No 10/2011 of January 14, 2011, and its subsequent amendments.

General labelling:

Product Name
Manufacturer name and address
Size and sizing chart
Lot number
Number of gloves inside the inner box
Production and expiry date
Use and storage instructions
EAN 13
A.Q.L. 1,5

Additional information:

FEATURE	Before aging	After aging
Tensile strength (ASTM)	18 MPa (mín.)	14 MPa (mín.)
Ultimate elongation (ASTM)	650% (mín.)	500% (mín.)

Labelling:

Pictograms* on labelling			
			
			
			
			

*The pictograms depicted here are for informational purposes. The product labeling may include specific technical information required by the standardization of the pictogram.